

Rubber Antioxidant -phenyl-p-phenylenediamine 4020 6PPD

Specifications :

Price	FOB\$6000-FOB\$7500
Brand Name	Loyal
Model Number	4020
Place of Origin	Shandong,China
Min.Order Quantity	12 tons
Payment Terms	T/T,L/C,D/P
Supply Ability	5000 tons/month
Delivery Detail	Within 20 days
Packaging Details	25kg/50kg bag

Detail Introduction :

Rubber Antioxidant 4020/6PPD

Chemical Name:N-(1,3-dimethyl-buty)-N'-phenyl-P-Phenylenediamine

Molecular:C18H24N2

CAS No.: 793-24-8

Molecular Weight: 268.40

HS code: 3812301000

As a kind of phenylene diamine rubber antioxidant, 6PPD has better compatibility with rubbers, seldom blooming, low volatility, low toxicity, excellent antioxidant, anti-ozone, anti-flex cracks ,good dispensability in sizing material and little effect on vulcanization, anti-insolation cracks, strong inhibition on copper ormanganese and other toxic metals, applicable to all types of synthetic rubber and natural rubber.

Appearance		Grey Purple to Purplish Brown Pastilles
Purity(GC),%	?	97.0
Melting Point(Initial),°C	?	45.0
Freezing Point,°C	?	46.0
Heat Loss(65-70°C),%	?	0.30
Ash,%	?	0.10

rubber antioxidant 6PPD



Basic information

Chemical name	N-(1,3-dimethyl-butyl)-N'-phenyl-P-Phenylenediamine
Molecular formula	C18H24N2
Executive standard	GB/T8826-2003
CAS NO	793-24-8
Appearance	Grayish-brown to black-brown granules
Initial Melting Point (%)	45 Min
Heat Loss (%) MAX	0.50
Ash (%) Max	0.15

Assay (%) MIN	96.0
Freezing point (%) MIN	45.5



Application:

-6PPD is an outstanding antioxidant and antiozonant, generally used for natural rubber and synthetic rubber.

-6PPD can slow rubber's fatigue degradation under static and dynamic operating conditions. It is an excellent stabilizer for natural rubber and synthetic rubber, with low pollution and low volatility.

Packaging Condition: Paper/plastic packages with a net weight of 25 kg per package.

Transportation Condition: Clear vehicle with ceiling, avoiding sunshine and rain, keeping away from hot source.



Tyre



Shoes



Rubber Belt



Rubber Gloves



Rubber Tape



Rubber Wire

Used as antiaging agent for rubber, suitable for natural rubber and synthetic rubber. Applications include pneumatic tire components, solid tires, conveyor belts, hose, tape, cables, automotive cushioning brackets, rubber joints and general rubber industrial products, all of which are in constant or intermittent dynamic working conditions requiring ozone protection.



Our service:

- 1, Professional factory production line!
- 2, Perfect delivery guarantee!
- 3, Sufficient stock to meet your large continuous orders!
- 4, Professional foreign traders offer you the best products, saving time and money. Preferential price and fast shipment delivery.

Armenia 7,320.00 USD

Jordan 22,790.00 USD

Canada 7,312.50 USD

Bangladesh 25,000.00 USD

Kazakhstan 11310.00 USD

Ecuador 33B; USD4546.70

Ukraine 33B; USD6490.00

Georgia USD2849.00

Germany 33B; USD3875.00

Nigeria 29. Total C&F Value in Figure 179,000.00

Pakistan 6,000.00 USD

NEW SANDA CHEMICAL

FQA?

Q: Are you a factory or trading company?

A: We are a factory.

Q: What documents you provide?

A: Usually, we provide Commercial Invoice, Packing List, Bill of loading, COA and Origin certificate. PLS let us know if your markets have any special requirements.

Q: What is the payment terms?

A: L/C , T/T, Western Union, Paypal, Escrow.

Q: How can I get some samples?

A: Kindly send us your address, we are honored to offer you samples.

Sample Time: 5-7 days.

The sample charge will be refund after confirm order.

Q: How does your factory do regarding quality control?

A: Our factory has gained ISO9001 2008, SGS authentication.

